

民用机场专用设备
审定合格证
AIRPORT EQUIPMENT CERTIFICATE

证书编号/Certificate No.: 06404467

有效期至/Expiration Date: 2014-11-24

根据《民用机场管理条例》(中华人民共和国国务院令第 533 号)规定,下列产品通过合格性审定,可以在民用机场内使用:

This certificate is issued in accordance with the P.R.CHINA State Council Order No.533, *The Regulation on Airport Management*, and certifies that the following equipment has passed the qualification examination for use in airport:

顺序闪光灯系统
Sequence Flash Lighting System

型号/Model: SSD-A

制造商/Manufacturer 上海航安机场设备有限公司
Airsafe Airport Equipment Co., Ltd.

地址/Address 上海市嘉定区徐行镇安新路 38 号
No.38 Anxin Road, Xuhang Town, Jiading District, Shanghai

设备外观&主要性能指标/ Basic Information



符合如下技术规范:

In Compliance With the Following Specifications:

- ICAO Annex 14. Vol.1
- FAA AC 150/5345-51
- FAA E-2628b&2698

备注 Notes:

1. 设备详细外观及性能指标作为本证书的一部分打印于本证书背面
Appearance and specifications of the equipment are printed overleaf as part of this certificate
2. 下列方框内的登记记录表示本证书所示内容发生了变更,变更具体内容打印于本证书背面
Records sealed below on the blanks indicate revisions of this certificate with explanations printed overleaf

--	--	--	--	--

颁发日期:
Issue Date:

2011-01-10





额定输入电压 Rated Input Voltage	AC 220V±10%,50Hz±1Hz
额定输入功率 Rated Input Power	≤3000W
控制方式 Control Method	本地或远端控制 Local or Remote Control
闪光频率 Flashing Frequency	每秒一次或两次,可调整 60 or 120 times pro second, adjustable
工作环境温度 Ambient Temperature	-55°C~+55°C
相对湿度 Relative Humidity	<95%
光强等级 Light Intensity	低亮度 Low intensity 3%(300±150CD) 中亮度 Middle Intensity 10%(1500±500CD) 高亮度 High Intensity 100%(15000±500CD)
光束分布 Beam Angle	水平 Hori: ±150 垂直 Vert: ±50
光源寿命 Lifespan of Lamp	>360 万次 More than 3,600,000 times
系统控制柜尺寸 Master Timer Dimensions (L×W×H)	600mm×600mm×1500mm
单元控制箱尺寸 Unit Control Box Dimensions (L×W×H)	380mm×300mm×124mm
单元闪光灯具尺寸 Dimension of light fixture (R×D×H)	φ270mm×245mm×299mm